

AIMING ANGLE:


L Beam Length
W Beam Width
C Distance to center beam

D Distance
A Aiming Angle
FC Footcandles


L and **W** are the outer points where the candle power drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.

Lamp data shown is typical. Consult lamp manufacturers for availability and performance.


0°




30° Horizontal



30° Vertical



45° Vertical



LAMP:

	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	D	FC	L	W	D	C	FC	L	W	D	C	FC	L	W	D	C	FC	L	W
	15°	50,000	7,500	15'	222	3.9'	3.9'	10'	5.8'	325	3.5'	3.0'	5'	8.7'	250	5.6'	2.6'	8'	8.0	276	4.3	3.0
				20'	125	5.3'	5.3'	15'	8.7'	144	5.3'	4.6'	8'	13.9'	98	8.9'	4.2'	12	12.0	123	6.4	4.5
				25'	80	6.6'	6.6'	20'	11.5'	81	7.1'	6.1'	11'	19.1'	52	12.2'	5.8'	16	16.0	69	8.6	6.0
				30'	56	7.9'	7.9'	25'	14.4'	52	8.8'	7.6'	14'	24.2'	32	15.6'	7.4'	20	20.0	44	10.7	7.4 9'
	26°	18,000	7,500	8'	281	3.5'	3.5'	7'	4.0'	239	4.2'	3.6'	3'	5.2'	250	6.2'	2.7'	5	5.0	255	4.7	3.1
				12'	125	5.3'	5.3'	10'	5.8'	117	6.0'	5.1'	4'	6.9'	141	8.3'	3.5'	7	7.0	130	6.5	4.4
				16'	70	7.1'	7.1'	13'	7.5'	69	7.8'	6.7'	5'	8.7'	90	10.4'	4.4'	9	9.0	79	8.4	5.6
				20'	45	8.9'	8.9'	16'	9.2'	46	9.6'	8.2'	6'	10.4'	63	12.5'	5.3'	11	11.0	53	10.3	6.9'
	60°	5,000	7,500	6'	139	6.9'	6.9'	5'	2.9'	130	8.7'	6.7'	2'	3.5'	156	N/A	4.6'	3	3.0	196	10.4	4.9
				8'	78	9.2'	9.2'	7'	4.0'	66	12.1'	9.3'	3'	5.2'	69	N/A	6.9'	5	5.0	71	17.3	8.2
				10'	50	11.5'	11.5'	9'	5.2'	40	15.6'	12.0'	4'	6.9'	39	N/A	9.2'	7	7.0	36	24.2	11.4
				12'	35	13.9'	13.9'	11'	6.4'	27	19.1'	14.7'	5'	8.7'	25	N/A	11.5'	9	9.0	22	31.2	14.7

Job Information

Type:

Lightolier a Genlyte Thomas Company

www.lightolier.com

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®